

# ColorWorks C831 Inkjet Label Printer

Contact Us 1-800-947-8247 x1

---



Epson's ColorWorks C831 industrial-strength inkjet label printer is ideal for GHS large format drum and chemical labels and more. It combines all the benefits of a rugged color inkjet printer with the accuracy of an 8-pin tractor feeder and is the first inkjet printing solution that has been BS5609 certified.

**Model:** C11CC68121

## Overview ▶

- Ideal for large labels including large-format drum and chemical labeling
- Industrial-strength inkjet printer with tractor feeder
- Fast print speeds of up to 16.5 pages per minute
- Printable area up to 8.0 x 22"
- Only inkjet solution that has been BS5609 certified<sup>1</sup>
- Supports a wide variety of media types and sizes

---

## Specifications ▶

## Print Other:

---

### Printing Technology:

MicroPiezo® inkjet technology

### Print Resolution:

720 dpi x 720 dpi maximum

### Print Width:

3.0 – 9.5 inches (76.2 – 241.3mm)

### Print Speed:

- Draft mode: 16.5 pages per minute
- Normal mode: 13.6 pages per minute
- Super fine mode: 7.0 pages per minute<sup>1</sup>

## Ink:

---

### Ink Type:

Pigment ink, individual CMYK cartridges<sup>3</sup>

### Ink Configuration:

- GJIC5(C) Cyan C13S020564
- GJIC5(K) Black C13S020563
- GJIC5(M) Magenta C13S020565
- GJIC5(Y) Yellow C13S020566

## General:

---

### Operating Systems:

- Windows® XP 32-bit (SP3)/64-bit (SP2)
- Vista® 32-bit/64-bit (SP2)
- Windows 7 32-bit/64-bit
- Windows Server 2003
- Windows Server 2008

### Temperature:

- Operating: 10–35 degrees C
- Storage: -20–40 degrees C

### Humidity:

- Operating: 20–80% RH humidity
- Storage: 5–85% RH humidity

### Sound Level:

- Silent feed on: approx. 48dB (A)
- Silent feed off: approx. 50dB (A)

### Dimensions:

18.3 x 18.3 x 8.8" (W x D x H)

### Weight:

Approx. 26 lbs (12.2kg) – without ink

### Safety Approvals:

- EMC standards: CNS13438 Class A
- Safety standards: BSMI (CN14336), Green Mark Program compliant, UL/C-UL, NOM, Argentine, CE, EN60950

## Fonts:

---

### Barcode:

Code 39, Code 128, Interleaved 2 of 5, EAN-13, EAN-8, UPC-A, UPC-E, POSTNET, QR Code

**Control Code:**

ESC/P Raster (undisclosed)

**Media Handling:**

---

**Width:**

3.0 – 9.5 inches (76.2 – 241.3mm)

**Type:**

Continuous paper (plain paper, label, medicine bags)

**Thickness:**

2.5 – 7.5 mils (0.065 – 0.19mm)

**Length:**

0.5 – 22.0 inches (12.7 – 558.8mm)<sup>2</sup>

**Feed Method:**

Push tractor feed (rear in/front out)

**Connectivity:**

---

**Standard Connectivity:**

Hi-Speed USB, Bi-directional parallel (IEEE-1284 ECP mode supported), Ethernet

**Display Terminal:**

---

**Ethernet:**

Ethernet 10/100 BASE-T

**Power:**

---

**Rated Voltage:**

AC 110–240 VAC

**Rated Frequency:**

50 – 60 Hz

**Power Consumption:**

- Printing: Approx. 20 W (mean, ISO/IEC 10561 letter)
  - Standby: Approx. 2.3 W (sleep mode)
-