

Mobilink P60II 2" Mobile Receipt or Label Printer

Contact Us 800.463.7766

Mon-Fri 6am-8pm, Sat 7am-4pm PT



The Mobilink ruggedized P60II has all the features you need to print receipts or labels anytime, anywhere. It offers the fastest printing in its class with speeds up to 100mm/second, an industry-leading battery life of up to 46 hours and flexible connectivity. And with Epson's unique ePOS-Print technology, the Mobilink P60II can print directly from any mobile devices running an iOS, Android or Windows operating system.

Overview ▶

- Compatible with iOS, Android and Windows mobile devices
- mPOS ready
- Industry-leading operational battery life up to 46 hours*
- 4-foot drop rating and IP54 environmental certified
- Highest printing speed in its class
- Supports 802.11a/b/g/n with 2.4GHz/5GHz compatibility and Bluetooth® 2.1 + EDR
- Offers paper-saving of up to 30%
- Print width to 54mm on standard 58mm media
- Zebra® emulation available for label applications

What's In The Box:

- Mobilink P60II Mobile Printer
- Battery

- Roll paper
- User's manual
- USB cable
- Belt clip
- 58mm spacer

Specifications

Print Other:

Printing Technology:

Thermal line printing

Print Resolution:

Dot / Line: 420/432 dots

Print Speed:

- Receipt mode: 100mm/sec
- Label mode: 80mm/sec
- Peeler mode: 40mm/sec

General:

Temperature:

Operating: 0° C to 45° C

Dimensions:

4.05" x 6.25" x 2.55" (103 x 159 x 65 mm) (W x D x H)

Weight:

- Receipt version: 1.4 lbs (630g) with battery, belt clip
- Label version: 1.3 lbs (600g) with battery, belt clip

Case Color:

Epson Black

Print Fonts:

Print Fonts:

Font A 12 x 24, new Font B 10 x 24, new Font C 8 x 16

Column Capacity:

58mm paper, Font A/B/C, 35/42/52 columns;60mm paper, Font A/B/C, 36/43/54 columns

Character Size:

1.5 x 3.0 / 1.25 x 3.0 / 1.0 x 2.0 mm (W x H)

Fonts:

Font A 12 x 24, new Font B 10 x 24, new Font C 8 x 16

Character Set:

95 Alphanumeric, 48 International, 128 x 10 Graphic

Characters per Inch:

17/20/25 cpi

Barcode:

- 1D: EAN-8, EAN-13, UPC-A, UPC-E, JAN13, JAN8, Code 39, Code 93, Code 128, ITF, CODEBAR, GS1-128, GS1 DataBar, GS1 DataBar Truncated, GS1DataBar Limited, GS1 DataBar Expanded
- 2D: QR Code, Maxi Code, PDF417, Composite, DataMatrix, RSS/GS1 and Aztec

Media Handling:

Width:

- Receipt Version: Paper or labels, 58mm or 60mm
- Label Version: Paper or labels, 30 – 60mm

Core Diameter:

51mm

Auto Cutter:

Partial cut, left uncut (receipt version)

Paper Loading:

Automatic label removal from backing (label version)

Connectivity:

Standard Connectivity:

802.11b/g/n (2.4GHz) and 802.11a/n (5GHz) or Bluetooth 2.1 + EDR

Printing from a Mobile Device:

Supported Mobile Operating Systems:

- Wi-Fi (802.11): iOS, Android and Windows® (Security Level WEP, WPA, WPA2-Enterprise)
- Bluetooth: iOS, Android and Windows

POS Details:

Reliability:

10 million printing lines; 500,000 autocutter (receipt version)

Drop Rating:

4 feet

Data Buffer:

4096 bytes

Sensors:

Paper out (receipt and label versions); Gap, black mark, label taken (label version)

Software Included:

TM-P60II Utility, EpsonNet Config, EpsonNet Simple Viewer, TM-P60II Remote Configuration Tool, TM Bluetooth Connector, Built-In Configuration Page

Audible Alert:

Programmable buzzer

LED Indicators:

- Green LED: Power (ON=Power on, OFF=Power off)
- Orange LED: Only shown when power is ON; Error, Paper end, Cover open, Battery level low (printer does not operate)
- Blue LEDs, Four battery level indicators:
 - 3 LED ON = approx. 100%–60%
 - 2 LED ON = approx. 60%–20%
 - 1 LED ON = approx. 20%–10%
 - 1 LED Flashing = approx. 10%–1%

Power:

Power Source:

Custom Lithium-Ion battery pack, AC adapter (option)

Battery Life:

Up to 27 hours with 802.11n, up to 46 hours with Bluetooth 2.1 + EDR¹

Charging:

AC adapter (2.5 hours to full charge), custom quad baycharger (2.5 hours to full charge)

Copyright © 2000-2018 Epson America, Inc.